

ALUMINUM SERVICE ENTRANCE CAP - CLAMP ON

FEATURES:

- Service entrance caps are used as a connecting point in an overhead service entrance and can be mounted on threaded or unthreaded Rigid Conduit, IMC or EMT Conduit
- Clamp-On Type
- Phenolic Insulator with Multiple Holes
- UL Listed for Use in Wet Locations
- UL Standards: UL 514B, CSA C22.2 No. 18

MATERIAL / FINISH

- Aluminum

ITEM#	UPC	TRADE SIZE (INCH)	DIMENSIONS			CASE QTY
			A	B	C	
OL-43336	665355943336	1/2"	2.68	2.50	2.19	20
OL-43343	665355943343	3/4"	3.04	2.76	2.39	20
OL-43350	665355943350	1"	3.48	2.96	2.58	20
OL-43367	665355943367	1-1/4"	4.22	3.27	3.06	20
OL-43374	665355943374	1-1/2"	5.22	4.28	3.49	20
OL-43381	665355943381	2"	6.68	5.81	4.33	20
OL-43398	665355943398	2-1/2"	9.94	7.05	6.54	5
OL-43404	665355943404	3"	11.69	8.54	6.93	5
OL-43411	665355943411	3-1/2"	11.69	8.54	7.28	5
OL-43428	665355943428	4"	11.69	8.54	7.86	5

