

ANTI-SHORT BUSHINGS

FEATURES:

- Insulates conductor from cut armor ends on flexible BX or Greenfield conduit
- Inserted into I.D. at termination point
- No tools needed for a secure assembly
- Overlapping horizontal flange protects against sharp metal edges
- Tapered design assures fast insertion
- Extra length assures positive grip
- Polypropylene material resists weather extremes oil, moisture and chemicals
- Rated up to 194°F

MATERIALS / FINISH

- Polypropylene

ITEM #	UPC	SIZE	CABLE SIZES	DIMENSIONS			
				A	B	C	D
OLASB0	743269375952	0	14/2, 14/3, 12/2	0.56"	0.67"	0.38"	0.312"
OLASB1	743269375969	1	14/4, 12/3, 6/1, 4/1	0.65"	0.67"	0.45"	0.312"
OLASB2	743269375976	2	12/4, 10/2, 10/3, 2/1	0.61"	0.859"	0.58"	0.125"
OLASB3	743269375983	3	10/4, 8/2, 8/3, 1/1	0.67"	1.046"	0.79"	0.109"
OLASB4	743269375990	4	8/4, 6/4, 6/3, 6/2, 4/3, 4/2	0.83"	1.266"	1.00"	0.156"

