

BLACK INSULATED CONNECTOR - IN-LINE SPLICE

FEATURES:

- One wire per terminal
- High-dielectric insulation — abrasion, chemical & UV resistant
- Pre-filled with oxide inhibitor
- Hex-head bolt for secure tightening
- Black color for easy identification
- Supports wire ranges from #14 to 750 MCM
- Maximum voltage rating: 600V
- Allows easy re-entry for changes, inspection, or troubleshooting
- Plugs are marked with max wire size for quick identification
- Wide temperature range: -49°F to 194°F (-45°C to 90°C)
- ANSI C119.4 & cULus 486B listed up to 750 MCM, 600V
- Rated for 194°F (90°C) copper and/or aluminum conductors
- For indoor use only

MATERIAL / FINISH:

- 6061-T6 Aluminum

ITEM#	UPC	WIRE RANGE	ALLEN HEX	WIRE PORTS	TORQUE (in/lbs)	MAX AMP (Cu)	MAX AMP (Al)	MIN QTY
OL-38486	665355938486	2-14	5/32	Inline Splice	28	130	100	16
OL-38493	665355938493	1/0-14	3/16	Inline Splice	180	170	135	15
OL-38509	665355938509	2/0-6	7/32	Inline Splice	110	195	150	15
OL-42413	655471242413	3/0-6	7/32	Inline Splice	110	225	175	12
OL-73138	655471473138	250-6	5/16	Inline Splice	110	290	230	7
OL-38523	665355938523	350-6	3/8	Inline Splice	110	350	280	4
OL-66338	655471466338	500-4	3/8	Inline Splice	150	430	350	6
OL-20547	655471020547	600-4	3/8	Inline Splice	550	475	385	5
OL-12129	655471112129	750-1/0	3/8	Inline Splice	550	535	435	2



SPECIFICATION SHEET

ITEM#	UPC	WIRE RANGE	ALLEN HEX	WIRE PORTS	WIDTH	HEIGHT	LENGTH	MIN QTY
OL-76220	655471176220	4-14	5/32	2	1.25	1.19	1.14	16
OL-38776	665355938776	4-14	5/32	3	1.25	1.19	1.56	8
OL-38783	665355938783	4-14	5/32	4	1.25	1.2	1.97	4
OL-38790	665355938790	4-14	5/32	5	1.25	1.2	2.38	5
OL-38806	665355938806	4-14	5/32	6	1.25	1.2	2.79	6
OL-38820	665355938820	4-14	5/32	8	1.25	1.2	3.62	8
OL-61449	655471461449	2-14	5/32	2	1.63	1.4	1.56	16
OL-38837	665355938837	2-14	5/32	3	1.63	1.4	1.93	12
OL-38844	665355938844	2-14	5/32	4	1.63	1.4	2.48	8
OL-38851	665355938851	2-14	5/32	5	1.63	1.4	3.03	7
OL-38868	665355938868	2-14	5/32	6	1.63	1.4	3.58	7
OL-38875	665355938875	2-14	5/32	7	1.63	1.4	4.13	8
OL-38882	665355938882	2-14	5/32	8	1.63	1.4	4.69	8
OL-60239	655471060239	1/0-14	3/16	2	1.75	1.6	1.61	18
OL-38899	665355938899	1/0-14	3/16	3	1.75	1.6	2.28	6
OL-38905	665355938905	1/0-14	3/16	4	1.75	1.6	2.95	9
OL-38912	665355938912	1/0-14	3/16	5	1.75	1.6	3.62	9
OL-38929	665355938929	1/0-14	3/16	6	1.75	1.6	4.29	6
OL-38936	665355938936	1/0-14	3/16	7	1.75	1.6	4.96	6
OL-38943	665355938943	1/0-14	3/16	8	1.75	1.6	5.63	2
OL-82659	655471482659	2/0-6	7/32	2	1.79	1.63	1.65	18
OL-38950	665355938950	2/0-6	7/32	3	1.79	1.63	2.32	6
OL-38967	665355938967	2/0-6	7/32	4	1.79	1.63	2.99	9
OL-38974	665355938974	2/0-6	7/32	5	1.79	1.63	3.66	9
OL-38981	665355938981	2/0-6	7/32	6	1.79	1.63	4.33	6
OL-38998	665355938998	2/0-6	7/32	7	1.79	1.63	5	6
OL-39001	665355939001	2/0-6	7/32	8	1.79	1.63	5.67	2
OL-91872	655471191872	3/0-6	7/32	2	1.97	1.77	1.81	6
OL-39018	665355939018	3/0-6	7/32	3	1.97	1.77	2.56	12
OL-39025	665355939025	3/0-6	7/32	4	1.97	1.77	3.31	8
OL-39032	665355939032	3/0-6	7/32	5	1.97	1.77	4.06	2
OL-39049	665355939049	3/0-6	7/32	6	1.97	1.77	4.41	2
OL-39056	665355939056	3/0-6	7/32	7	1.97	1.77	5.16	2
OL-39063	665355939063	3/0-6	7/32	8	1.97	1.77	5.91	4
OL-84430	655471184430	250-6	5/16	2	2.38	2.15	2.2	6
OL-08987	655471408987	250-6	5/16	4	2.38	2.15	4.02	3
OL-57407	655471357407	350-6	3/8	4	2.78	2.5	4.53	2
OL-65265	655471065265	500-4	3/8	4	3.03	2.8	5.16	3



130 NY-59
BUILDING D, UNIT 101
AIRMONT NY 10901

845-513-0344
SALES@OHLECTRIC.COM
WWW.OHLECTRIC.COM

SPECIFICATION SHEET

WIRE SIZE	CONNECTOR SIZE										
	750	600	500	350	250	3/0	2/0	1/0	1	#2	#4
	TORQUE VALUE (in/lbs.)										
600-750	442										
600	442	398	310								
500	442	398	310								
400	310	398	310								
350	310	398	310	221							
250	310	398	310	221	149						
4/0			310	221	149						
3/0			310	221	149	100					
2/0			310	221	149	100					
1/0			310	221	149	100	89	89			
#3 - #1			310	221	149	100	89	89	89	80	
#4 - #6			310	221	149	100	89	89	89	80	35
#8							89	89	89	80	35
#10 - #14							89	89	89	80	35

ITEM#	UPC	WIRE RANGE	ALLEN HEX	WIRE PORTS	TORQUE (in/lbs)	MAX AMP (Cu)	MAX AMP (Al)	MIN QTY
OL-38486	665355938486	2-14	5/32	Inline Splice	28	130	100	16
OL-38493	665355938493	1/0-14	3/16	Inline Splice	180	170	135	15
OL-38509	665355938509	2/0-6	7/32	Inline Splice	110	195	150	15
OL-42413	655471242413	3/0-6	7/32	Inline Splice	110	225	175	12
OL-73138	655471473138	250-6	5/16	Inline Splice	110	290	230	7
OL-38523	665355938523	350-6	3/8	Inline Splice	110	350	280	4
OL-66338	655471466338	500-4	3/8	Inline Splice	150	430	350	6
OL-20547	655471020547	600-4	3/8	Inline Splice	550	475	385	5
OL-12129	655471112129	750-1/0	3/8	Inline Splice	550	535	435	2



OHLELECTRIC®

130 NY-59
BUILDING D, UNIT 101
AIRMONT NY 10901

845-513-0344
SALES@OHLELECTRIC.COM
WWW.OHLELECTRIC.COM